

Advanced Switching & Magnetic Sensing Solutions

66 Whitecap Drive, North Kingstown, RI 02852 USA

ISO 9001

California Proposition 65 STATEMENT

Company Name: Coto Technology
Company Address: #50 Galaxia Parque Industrial I , Col. Alamitos CP 21100
Contact Person: Ethel Elvira Najera
E-mail: Ethel.najera@Cotorelay.com
All products supplied to Coto technology. This letter is to confirm that the product(s) referenced bellow have been evaluated against California Proposition 65.
Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986) is a Californian law that requires businesses to notify Californians about significant chemicals that cause cancer or birth defects or other reproductive harm. The law requires that no person doing business, knowingly and intentionally expose an individual to a chemical known to the state of California to cause cancer, birth defects, or reproductive toxicity without first giving a clear and reasonable warning. The Prop 65 list can be accessed at https://oehha.ca.gov/proposition-65/proposition-65-list
The compliance status of the product is confirmed by the sections below:
⊠The product(s) referenced above <u>DO NOT CONTAIN</u> any of the listed substances from the California Proposition 65 list.
☐ The products(s) referenced above have been evaluated for the presence of any substances from the California Proposition 65 list. The product(s) MAY CONTAIN the following substances, as provided in the table on the following page. (Table must be completed if this option is selected.)

Tel: 401-943-COTO Fax: (401) 942-0920 **www.cotorelay.com**

California Prop 65 Rev date: December 7, 2021

COTOMOS ®

Product Series	Package Type	Item weight (grams)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL	Comments
CT1XX	6-pin DIP	0.475	Sn100	250C / 30Sec. Reflow	R353	2	Comments
CT3XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	2	
CT4XX	6-pin DIP	0.475	Sn100	250C / 30Sec. Reflow	R353	2	
CT6XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	2	
CT7XX	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	2	
CTA17	8-pin DIP	0.510	Sn100	250C / 30Sec. Reflow	R353	2	
	·						
CS1XX	6-pin SMD	0.455	Sn100	250C / 30Sec. Reflow	R353	2	
CS3XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	2	
CS4XX	6-pin SMD	0.455	Sn100	250C / 30Sec. Reflow	R353	2	
CS6XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	2	
CS7XX	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	2	
CSA17	8-pin SMD	0.490	Sn100	250C / 30Sec. Reflow	R353	2	
C2XXS	4-pin SOP	0.085	Sn100	250C / 30Sec. Reflow	R353	2	
C3XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	2	
C5XXS	4-pin SOP	0.085	Sn100	250C / 30Sec. Reflow	R353	2	
C6XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	2	
C7XXS	8-pin SOP	0.180	Sn100	250C / 30Sec. Reflow	R353	2	

TMR PRODUCTS

Ī			Item					Comments
		Package	weight	Termination	Maximum Process	Compliance		
	Product Series	Туре	(grams)	Lead finish	Temp/Time	date code	MSL	
	RR1XX	SOT Family	0.014	N/A	260C	1540	1	

REED RELAYS

Product Series	Package Type	Item weight (grams)	Termination Lead finish	Maximum Process Temp/Time	Compliance date code	MSL	Comments
12XX	Potted THT	6.17	Sn100	270C / 10 Sec. Wave	0525	1	
13XX	Potted THT	26.47	Sn100	270C / 10 Sec. Wave	0525	1	
22XX	Potted THT	1.48	Sn100	270C / 10 Sec. Wave	0525	1	
2400-0058	Potted THT	3.62	Sn 100	270C / 10 Sec. Wave	0908	1	
23XX	Potted THT	2.48	Sn100	270C / 10 Sec. Wave	0525	1	
26XX	Potted THT	2.60	Sn100	270C/ 10 Sec. Wave	0525	1	
29XX	Potted THT	1.94	Sn100	270C / 10 Sec. Wave	0525	1	Excludes 2920 models due Hg content
35XX	Potted THT	10.07	Sn100	270C / 10 Sec. Wave	0525	1	Excludes 3520 models due Hg content
36XX	Potted THT	13.18	Sn100	270C / 10 Sec. Wave	0525	1	•
4XXX	Potted THT	3.06	Sn100	270C / 10 Sec. Wave	0525	1	
55XX	Potted THT	39.40	Sn100	270C / 10 Sec. Wave	0525	1	
58XX	Potted THT	18.59	Sn100	270C / 10 Sec. Wave	0525	1	
7XXX	Potted THT	8.39	Sn100	270C / 10 Sec. Wave	0525	1	Excludes 7200 models due Hg content
82XX	Potted THT	5.04	Sn100	270C / 10 Sec. Wave	0525	1	
83XX	Potted THT	4.36	Sn100	270C / 10 Sec. Wave	0525	1	
86XX	Potted THT	6.86	Sn100	270C / 10 Sec. Wave	0525	1	
87XX	Potted THT	73.56	Sn100	270C / 10 Sec. Wave	0525	1	
8000/8L	Molded THT	2.22	Sn100	270C / 10 Sec. Wave	0540	1	8061/8L61 are SMT type
9000	Molded THT	1.56	Sn100	270C / 10 Sec. Wave	0545	1	
9007	Molded THT	1.56	Sn100	270C / 10 Sec. Wave	0545	1	
9011	Molded THT	0.64	Sn100	270C / 10 Sec. Wave	0501	1	
9012	Molded THT	0.82	Sn100	270C / 10 Sec. Wave	0501	1	
9090	Molded THT	0.92	Sn100	270C / 10 Sec. Wave	0501	1	
9091	Molded THT	0.92	Sn100	270C / 10 Sec. Wave	0501	1	
9092	Molded THT	1.24	Sn100	270C / 10 Sec. Wave	0501	1	
9094	Molded THT	0.95	Sn100	270C / 10 Sec. Wave	0501	1	
9081	Molded THT	2.20	Sn100	270C / 10 Sec. Wave	0501	1	
9104	Molded THT	3.08	Sn100	270C / 10 Sec. Wave	0501	1	
9117	Molded THT	0.60	Sn100	270C / 10 Sec. Wave	0501	1	

Coto Technology, Inc. Page 3

92XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0812	2	RoHS Compliance by exemption 7(a) see note 3
929X	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0816	2	RoHS Compliance by exemption 7(a) see note 3
93XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0641	2	RoHS Compliance by exemption 7(a) see note 3
94XX	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0805	2	RoHS Compliance by exemption 7(a) see note 3
9852	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0825	2	RoHS Compliance by exemption 7(a) see note 3
9802/9814	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0748	2	RoHS Compliance by exemption 7(a) see note 3
99XX's	Molded SMT	0.20	Gold flash	260C / 60 Sec. Reflow	0601	2	RoHS Compliance by exemption 7(a) see note 3
B21C	Molded BGA	0.20	N/A	260C / 60 Sec. Reflow	TBD	5A	
B41	Molded BGA	0.20	N/A	260C / 60 Sec. Reflow	1204	5A	RoHS Compliance by exemption 7(a) see note

Continue on next page

MOLDED SWITCHES

		Item					
	Package	weight	Termination	Maximum Process	Compliance		
Product Series	Type	(grams)	Lead finish	Temp/Time	date code	MSL	Comments
CT05	Molded SMT	0.12	Sn100	260C / 60 Sec. Reflow	0501	1	
CT10	Molded SMT	0.14	Sn100	260C / 60 Sec. Reflow	0501	1	
CM10	Molded SMT	0.12	Sn100	260C / 60 Sec. Reflow	0501	2	
MN / MN2S	SMT	0.12	Sn100	260C / 60 Sec. Reflow	0437	2	

REED SWITCHES

		Item					
	Package	weight	Termination	Maximum Process	Compliance		
Product Series	Type	(grams)	Lead finish	Temp/Time	date code	MSL	Comments
FR / FR2S / FRB	SMT	0.12	Sn100	260C / 60 Sec. Reflow	0437	1	Discontinued